

가 : , core boxes() CNC 가 .

- 가
- 가

	-	
at 23°C	ISO 2781 :1988	1.30

AT 23°C			
	ISO 868-85	Shore D1	85
	ISO 5470-1 :1999	mm ³	160
	ISO 604-97	Mpa	68
	ISO 178-93	Mpa	75
	ISO 178-93	MPa	1,900
	ISO 527-96	MPa	46
	ISO 527-96	%	8.5
(unnotched specimens)	ISO 179/1D-94	kJ/m ²	30
	T.M.A.-Mettler	°C	90
(CTE) [+10, +80]°C	T.M.A.-Mettler	10 ⁻⁶ .K ⁻¹	95

Axson LAB 920 GN 400 g/m2 H 9951 (가 가)
H8110 BU (가) 가 가 .



LAB 920 GN « NEW »

가

가)		
	Cut speed (Cs in m/min)	Speed per rotation for 1 tooth (mm/tr)
Rough shape	100 to 400	0.30
Finish	400	0.06

: cutting taper 0 .

:

-
-
- 가

(MSDS) .

1000 x 500 x 100 mm
1000 x 500 x 75 mm
1000 x 500 x 50 mm

The information of our technical data sheet are based on our present knowledge and the result of tests conducted under precise conditions. It is the responsibility of the user to determine the suitability of AXSON products, under their own conditions before commencing with the proposed application. AXSON refuse any guarantee about the compatibility of a product with any particular application. AXSON disclaim all responsibility for damage from any incident which results from the use of these products. The guarantee conditions are regulated by our general sale conditions.